

## Cargo Hold Cleaning

### General Features:

- Maximizing the effectiveness of chemical
- Eliminating the quantities of chemicals to the minimum possible
- Spraying simply and quickly
- Running smoothly

### Instructions for use :

#### 1. Installing the HANGING DEVICE

- Calculate the maximum height that needs to be reached in cargo hold and choose equivalent lengths of guide pipe line and spraying hose. Lower the above items down the cargo hold.
- Cover the full length of spraying hose with the 1.8m parts of guide pipe line and connect them to each other.
- Lower the HANGING DEVICE by slacking the wire block manually down the cargo hold.
- Check all connections are safely secured.

#### 2.Formatting HCP50

- Using a high pressure hose at a desired length, fix the one end to the supply connection of HCP50 and the other to the gun handle at the lower end of chemical pipe. HCP50 suction should be connected to a polypropylene hose with the other end of the hose in the drum with chemical.

#### 3. Rinsing off with high pressure

- Disconnect the spray nozzles pipe and connect the high pressure nozzle. Disconnect the hose from the chemical pump and connect it to a water high pressure machine. Rinsing off procedure

### Technical Data

Duct Dimensions	38mm
Duct Length	3000~3250mm
Duct Quantity	6pcs
Overall Length	18m
Weight	60Kg
Pulley	2pcs
Rope Length	40m

